



XICHENG EP LTD

Product name:	Ventilation air duct
Material:	PPs flame retardant material
Working temperature:	-15℃ to 80℃
Structure:	injection molding
Characteristics:	Acid and alkali corrosion resistance, excellent sound insulation performance, smooth outer wall, anti-condensation, less heat loss, light weight, easy installation and operation, and has weldability, etc.
Product picture:	
Color:	Beige/Grey
Product certification:	ISO9001, ISO14001, RoHS, SGS, REACH
Application fields:	Any field that needs ventilation under normal temperature conditions, such as laboratory ventilation, workshop and warehouse ventilation, daily life exhaust, etc.

Size(outer size)	Thickness	Unit	Weight	Length	Function
φ20mm	2.8mm	piece	0.5	4 meters	For ventilation & drainage
φ25mm	2.8mm	piece	0.6	4 meters	
φ32mm	3.5mm	piece	1	4 meters	
φ40mm	4mm	piece	1.3	4 meters	
φ50mm	4mm	piece	1.8	4 meters	
φ63mm	4.5mm	piece	3.65	4 meters	
φ75mm	5mm	piece	4.34	4 meters	
φ90mm	5mm	piece	5.19	4 meters	
φ110mm	3mm	piece	2.6	3 meters	
φ160mm	3mm	piece	4.5	3 meters	
φ200mm	3.3mm	piece	6	3 meters	
φ250mm	4mm	piece	9	3 meters	
φ315mm	4.2mm	piece	12	3 meters	
φ355mm	4.2mm	piece	14.4	3 meters	
φ400mm	4.5mm	piece	16.8	3 meters	
φ450mm	4.8mm	piece	20	3 meters	
φ500mm	5.5mm	piece	23.5	3 meters	